

M 200

Closed system corrosion inhibitor

DESCRIPTION

M200 is a blended corrosion and scale inhibitor designed for use in all types of closed loop systems including glycol loops, chilled water systems, hot water systems, process loops and alcohols. By combining Molybdate chemistry with supplemental inhibitors and pH buffers, this balanced formulation will protect multi-metal systems including iron, mild steel, bronze, copper, and copper alloys. The yellow metal inhibitor (tolytriazole) used in the formulation ensures superior protection of copper and copper alloys for an extended period of time. M200 is compatible with ethylene or propylene glycol and can be used to re-inhibit glycol solutions or can be used as the initial inhibitor package. M200 also contains an effective polymer to prevent and disperse any hardness deposits that may form in the system when using hard water make-up.

TYPICAL APPLICATIONS

- Compatible with Ethylene Glycol, Propylene Glycol, Glycol Solutions or Alcohols
- Chilled or Hot Water Heating Systems, Process Heating or Cooling Systems

BENEFITS

- Superior corrosion protection
- Will not cause staining
- Concentrated formula
- Compatible with glycol solutions and alcohols

DOSAGE & CONTROL

For effective corrosion control, maintain Molybdate concentrations between 50 – 150 mg/L. A periodic Molybdate test should be performed to ensure that Molybdate levels are within the recommended control range. The dosage of M200 will vary depending on system operating conditions and water quality. The recommended minimum dosage is 1.5 – 2.5 liters per each 1000 liters of untreated system volume. M 200 may be fed without dilution directly to the system via a by-pass or pot-feeder. It may also be fed by a chemical pump to an area of good mixing within the system. No special materials of construction are required for the chemical feed system.

PACKAGING & DELIVERY

M200 is available in 20 Liter pails, 205 Liter drums, totes and bulk. The product containers should be kept tightly closed. Protect from freezing.

PRODUCT SAFETY

M200 should be handled with appropriate care. All plant personnel who may have contact with M200 should review the Material Safety Data Sheet to familiarize themselves with the application, handling, storage and disposal procedures before using this product

Technical Bulletin No.: M2003700 CAN. Recommendations given in this bulletin are based on tests believed to be reliable. However, the use of the product is beyond the control of Vedra Industries, and no guarantees, expressed or implied, are made as to the effects of such or the results to be obtained if not used in accordance with directions or established safe practice. The buyer must assume all responsibility, including injury or damage, resulting from misuse of the product as such, or in combination with other material. This bulletin is not to be taken as a license to operate under or recommendation to infringe any patent.